

*- reliability - service -*  
Cemintel™ External Texture Coating System

www.cemintel.com.au

*external texture*  
**coating system**

The Cemintel™ Fibre Cement External Texture Coating System is a complete, three part jointing and coating system designed specifically for use over Cemintel™ Texture Base Sheet and Rendaline™. Typical applications include new homes, second storey additions and renovation of existing homes.



The system has been developed so that applicators and builders will have the confidence in using a complete warranted system, when used on Cemintel™ Texture Base Sheet and Cemintel™ Rendaline™.

Where to find us

**Cemintel™ Fibre Cement Systems**

**Web Site**

www.cemintel.com.au

**Cemintel™ Fibre Cement Systems**

**Sales Support**

Telephone: 13 17 44

Facsimile: 1800 646 364

**CSR™ designLINK®**

**Technical Support Service**

Telephone: 1800 621 117

**New South Wales and ACT**

376 Victoria Street,  
Wetherill Park NSW 2164

**Queensland**

768 Boundary Road,  
Coopers Plains QLD 4108

**Victoria**

277 Whitehall Street,  
Yarraville VIC 3013

**South Australia**

Lot 100, Sharp Court,  
Mawson Lakes SA 5095

**Western Australia**

21 Sheffield Road,  
Welshpool WA 6106

**Tasmania**

PO Box 61,  
Glenorchy TAS 7011

**Northern Territory**

Cnr Stuart Highway + Angliss Road,  
Berrimah NT 0828

**New Zealand**

147 Gracefield Road,  
Seaview, Wellington  
Ph 04 5684520

Warranty

Under no circumstances will CSR™ be liable for defects arising from poor workmanship of defective materials not supplied by CSR™. Any warranty claim must be made within 30 days of the alleged defect becoming apparent. If a CSR™ product does not meet our standard, we will, at our option, replace or repair it, supply an equivalent product, or pay for doing one of these.

This warranty excludes all other warranties and liability for damage or loss in connection with defects in CSR™'s product other than those compulsorily imposed by legislation, notably the Trade Practices Act.

YOUR DISTRIBUTOR'S CONTACT DETAILS

CSR™ is a trademark of CSR™ Building Products.

Published by Cemintel™ Fibre Cement Systems CSR Building Products, ABN. 55 008 631 356  
Cemintel™ External Texture Coating System Guide

*superior  
performance  
fully warranted  
simple to use*



reliability - service - support - leading-edge - reliability - service -  
complete jointing system - easy to apply - long lasting - superior performance - full warranty - simple as 1-2-3!

The **Cemintel™ External Texture Coating System** is easy to use and quality assured. The system is long lasting and is the only external jointing and coating system available that is fully warranted from cladding to coating.

smooth the way  
for a textured finish



### The Cemintel™ External Texture Coating System includes

- Cemintel™ Texture Base Sheet and CSR Rendaline™.
- Cemintel™ External Jointing Compound
- Cemintel™ External Jointing Tape
- Cemintel™ Skim Coat
- Cemintel™ Texture Coat
- All the correct tools: plastic trowel, stainless steel trowel and stainless steel broad knife.



### As simple as 1-2-3!

The Cemintel™ External Texture Coating System is a simple three part process

1. Fill the joint recess with **Cemintel™ External Jointing Compound**. Embed **Cemintel™ External Jointing Tape** into the compound with the smooth side out. Apply Cemintel™ External Jointing Compound evenly over the tape using a stainless steel broad knife.
2. Apply **Cemintel™ Skim Coat** in the same direction as the joint using a stainless steel trowel.
3. Apply **Cemintel™ Texture Coat** using a stainless steel and plastic trowel. Then apply final paint finish using a standard paint roller.



See the Cemintel™ Texture Base Sheet technical brochure for drying times and further information on installation recommendations and procedures for this system.